

DECLARATION OF PERFORMANCE According to Construction Products Regulation EU N° 305/2011

DoP Ref: GLT- 241-DoP-3

1. Unique Product identification code: 80-202

 Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
MKII-HR Fyreye MKII conventional Rate of Rise heat detector

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Fire detection and fire alarm systems installed in and around buildings. (Indoor use only)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

Zeta Alarms Limited 72-78 Morfa Road Swansea SA1 2EN UK

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

Not applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 1

7. In case of the declaration of performance concerning a construction product covered by the harmonized standard:

BRE GLOBAL, IRELAND (Identification No 2832) performed type testing and the initial inspection of the manufacturing plant and of the factory production control with continuous surveillance assessment and approval of the factory production control under system 1 and issued the EC certificates of conformity:

2831-CPR-F0071

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

Not applicable, see item 7



9. Declared performance:

All requirements including all Essential Characteristics and the corresponding performances for the intended use or uses indicated in 3. have been determined as described in the hEN mentioned in the following table.

Essential characteristics	Performance	Harmonized Technical Specification
		EN54-5: 2000 A1: 2002, A2: 2006
Nominal activation conditions /	Pass	4.2 - Classification
Sensitivity, Response delay		4.3 - Position of heat sensitive elements
(response time) and		5.2 - Directional dependence
Performance under fire		5.3 - Static response temperature
conditions		5.4 - Response times from typical application temperature
		5.5 - Response times from 25 °C
		5.6 - Response times from high ambient temperature (dry heat operational)
		5.8 - Reproducibility
		6.2 - Test for suffix R detectors
Operational reliability	Pass	4.4 - Individual alarm indication
		4.5 - Connection of ancillary devices
		4.6 - Monitoring of detachable detectors
		4.7 - Manufacturer's adjustments
		4.8 - On-site adjustment of response behaviour
		4.9 - Marking
		4.10 - Data
		4.11 - Additional requirements for software controlled detectors
Tolerance to supply voltage	Pass	5.7 - Variation in supply parameters
Durability of operational reliability and response delay,	Pass	5.9 - Cold (operational)
Temperature resistance		5.10 - Dry heat (endurance)
Durability of operational	Pass	5.14 - Shock (operational)
reliability,		5.15 - Impact (operational)
Vibration resistance		5.16 = Vibration, sinusoidal (operational)
		5.17 - Vibration, sinusoidal (endurance)
Durability of operational	Pass	5.11 - Damp heat, cyclic (operational)
reliability,		5.12 - Damp heat, steady state (endurance)
Humidity resistance		
Durability of operational	Pass	5.13 - Sulphur dioxide (SO2) corrosion (endurance)
reliability,		
Corrosion resistance		
Durability of operational	Pass	5.18 - Electromagnetic compatibility (EMC), immunity tests (operational)
reliability,		
Electrical stability		

10. The performance of the product identified in 1. and 2. is in conformity with the declared performance in 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in 4.

Signed for and on behalf of Zeta Alarms Limited by:

Name: N.R. P. Jones

Signature:

Position: Technical Manager

Place of issue: Swansea

Date of issue: 2nd December 2020